

Swivel Ring Hanger

Model: SD-HB

Designed for the suspension of non-insulated stationary pipe lines. To use as pipe support in-line with NFPA 13 requirements. The insert nut allows a vertical adjustment after installation, is tapped to NFPA reduced rod size standards.




Product Specifications:

Available Size	1/2" - 8"		
Material	Low Carbon Steel		
Standards	ASTM B633, ISO 10683		
Application	Water, HVAC & Fire-Fighting		
Coating Finish	Pre-Galvanized coil adheres to ASTM A653 G90 Low Carbon Steel - Electro-Galvanized to ASTM B633 Low Carbon Steel - Hot Dipped Galvanized to ASTM A123 Low Carbon Steel - Zinc Flake Coating to ISO 10683		
Approvals/Listings	Federal Specification WW-H-171E & A-A-1192 (Type 10) Manufacturer's Standardization Society MSS SP-69 & SP-58 (Type 10) UL Listed & FM Approved		



Swivel Ring Hanger

Product Dimensions:



Pipe Size	Rod Size		Test Load			
Inch	A Inch	B Inch	C Inch	D Inch	E Inch	Lb-f.
1/2	3⁄8	17⁄8	17⁄ ₁₆	23⁄4	3½ ₁₆	750
3/4	3⁄8	1 ¹¹ / ₁₆	11⁄8	21/2	3 ¹ / ₁₆	750
1	3⁄8	15/8	1	21/2	3 ³ / ₁₆	750
11⁄4	3⁄8	1 ¹⁵ / ₁₆	11/16	2 ¹³ / ₁₆	3 ⁹ / ₁₆	750
11/2	3⁄8	21/8	11/16	31⁄8	31/8	750
2	3⁄8	2 ⁷ / ₁₆	11⁄8	3 ⁵ / ₁₆	43⁄8	750
21/2	3⁄8	23/4	11⁄4	3 ¹¹ / ₁₆	5	940
3	3⁄8	21/8	11⁄8	3¾	5% 16	1060
31/2	3⁄8	33⁄8	13⁄8	4 ⁵ / ₁₆	6 ⁵ / ₁₆	1250
4	3⁄8	31/8	1½	41⁄2	7	1500
5	1/2	45/8	15⁄8	55⁄8	83/8	2000
6	1/2	5 ⁵ / ₈	21⁄4	6½	9 ¹³ / ₁₆	2650
8	1/2	6 ¹³ ⁄ ₁₆	27/_16	7 ¹⁵ ⁄ ₁₆	121⁄4	4050

Note: • Swivel Nut is coming along with hanger. • Swivel Nut is available for 10mm and 12mm Rod size. • Swivel Hanger is also available in SS material upon request.



Swivel Ring Hanger

Miscellaneous Data:

1. Ordering Information

Example: SD-HB-1-4

- SD-HB is the part number
- (1) Electro-Galvanized Coating (2) Hot Dipped Galvanized Coating (3) Zinc Flake Coating
 (3) Pre-Galvanzied Coating
- (4) Size

2. Contact Information

For further information on any aspect of the SHIELD Pipe Supports please contact below:

MIDDLE EAST & AFRICA	UNITED KINGDOM			
Jebel Ali Free Zone, Dubai, UAE	Unit 3, Endeavor Drive, Basildon-Essex,			
P.O Box: 61199	SS3 14WF			
Tel.: +971 4 881 2070	Tel.: +44 1708 377731			
Fax: +971 4 881 2198	Fax: +44 1708347637			
Email: shieldme@shielglobal.com	Email: shielduk@shielglobal.com			