

U-Bolt

Model: SD-UB

- Designed to use as a support, anchor or guide for various types of pipes.
- High load capacity due to one piece design.
- Supplied with two nuts and washers.
- Special U bolts with longer tangents and threads can be furnished upon request.




Product Specifications:

Available Size	1/2" - 24"
Material	Mild Steel
Standards	ASTM B633
Application	Water, HVAC & Fire-Fighting
Coating Finish	Electro-Galvanized as per ASTM B633 Standards
Approvals/Listings	<p>Federal Specification WW-H-171E & A-A-1192A (Type 8) Manufacturers Standardization Society ANSI/MSS SP-69 & SP-58 (Type 24) UL Listed Approved</p> 

U-Bolt

Product Dimensions:



Pipe Size	Pipe O.D.	Dimensions			
		D	C	F	G
Inch	mm	Inch	Inch	Inch	Inch
½	21.3	M8	31	35	35
¾	26.7	M10	39	40	38
1	33.4	M10	45	45	40
1¼	42.2	M10	54	55	45
1½	48.3	M10	60	55	45
2	54.0	M10	72	60	45
2½	60.3	M10	86	75	55
3	67.0	M10	102	80	55
4	73.0	M10	128	95	55
6	82.0	M12	184	130	70
8	88.9	M12	239	155	70
10	101.6	M20	273	370	100
12	110.0	M20	324	420	100
14	114.3	M20	356	455	100
16	126.0	M20	406	505	100
18	141.3	M24	457	555	100
20	148.0	M24	508	605	100
24	155.0	M24	610	710	100

- Note:
- Measurements are subject to 5% tolerance.
 - Other Sizes available on request.
 - U Bolt sizes can be modified to match with Rubber support inserts.
 - Alternate rod sizes for different pipe sizes are also available.
 - Hot Dipped Galvanized can be supplied upon request.

U-Bolt

Miscellaneous Data:

1. Ordering Information

Example: SD-UB-1-4

- SD-UB is the part number
- (1) Electro-Galvanized Coating
- (4) Size

2. Contact Information

For further information on any aspect of the SHIELD Pipe Supports please contact below:

MIDDLE EAST & AFRICA	UNITED KINGDOM
Jebel Ali Free Zone, Dubai, UAE P.O Box: 61199 Tel.: +971 4 881 2070 Fax: +971 4 881 2198 Email: shieldme@shielglobal.com	Unit 3, Endeavor Drive, Basildon-Essex, SS3 14WF Tel.: +44 1708 377731 Fax: +44 1708347637 Email: shielduk@shielglobal.com