

# Model BVAVA-300 Quick Opening Ball Valves Sizes 1/2 inch to 2 inch NPS and BVAVFS-300 sizes 1/2inch and 3/4 inch NPS

Product Description

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
BVAVA-300	Stainless Steel Ball Valve	1/2, 3/4, 1, 1 1/4, 1 1/2, 2	(15, 20, 25, 32, 40, 50)	300	(2065)	a
BVAVFS-300	Stainless Steel Ball Valve	1/2, 3/4	(15, 20)	300	(2065)	a

Remarks:  
a. Valve supplied with ASME B1.20.1, BS EN 10226-1, and GB/T 7307 end connections with internal threads.

Details

Category	Quick Opening Valves
Class of Work	1140 - Valves (QOT), Ball
Approval Standard	FM 1140 - Quick Opening Valves 1/4 Inch Through 2 Inch Nominal Size
Certification Type	FM Approved
Listing Country	United Kingdom

Company

Shield Fire Safety and Security Ltd  
Unit 3 Endeavor Drive, Basildon, Essex, SS14 3WF, United Kingdom  
<http://www.shieldglobal.com>

Additional Info

Automatic Sprinkler Systems

Valves

Miscellaneous Valves

Quick Opening Valves

Manually operated ball valves are used to control water to small open-head extinguishing systems or in the trim on waterflow alarm valves, dry pipe valves or automatic water control valves.

The friction loss through these valves should be considered when they are used in hydraulically calculated extinguishing systems. Consult the manufacturer for details. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.