

Model MV-AS, MV-A, MV-E, MV-BS, MV-B

Product Description

Model No	K-Factor	Nominal Spray Angle	Nominal Thread Size		Finishes
			in	(mm)	
MV-AS	1.26	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-AS	1.54	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-AS	2.10	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-AS	2.45	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-AS	2.87	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-A	1.26	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-A	1.54	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-A	2.10	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-A	2.45	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-A	2.87	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-A	3.57	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-A	4.48	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-A	5.53	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-A	6.37	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-A	7.14	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-E	1.26	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-E	1.54	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-E	2.10	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-E	2.45	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-E	2.87	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-E	3.57	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-E	4.48	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-E	5.53	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-E	6.37	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-E	7.14	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Brass, Chrome, Electroless Nickel Plated, Epoxy Powder Coated
MV-BS	1.26	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-BS	1.54	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-BS	2.10	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-BS	2.45	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-BS	2.87	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-B	1.26	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-B	1.54	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-B	2.10	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-B	2.45	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-B	2.87	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-B	3.57	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-B	4.48	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-B	5.53	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-B	6.37	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel
MV-B	7.14	65°, 80°, 90°, 100°, 110°, 120°, 140°	1/2	(15)	Stainless Steel

Nozzles are Approved with an optional blow-off plug

Details

Category	Fixed Extinguishing Systems, Water-Spray, Open Water-Spray Nozzles
Class of Work	2025 - Open Spray Nozzles-Fixed Sys
Approval Standard	FM 2021, 2025 - Automatic and Open Water-Spray Nozzles for Installation in Permanently Piped Systems
Certification Type	FM Approved
Listing Country	United Kingdom

Company

Rapidrop Global Limited
Rutland Business Park, Newark Rd, Peterborough
PE1 5WA, United Kingdom
<http://www.rapidrop.com>