

# Models SD-PRV105 and SD-PRV205

## Product Description

Pressure Restricting Hose Valves, Angle

Model SD-PRV105 and SD-PRV205

## Product Specification

Model No	Description	Valve Size		Rated Working Pressure	
		in	(mm)	psi	(kPa)
SD-PRV105	Female NPT x Male NH Female NPT x Female NPT	1 1/2	(38)	175	(1205)
SD-PRV105	Female NPT x Male NH Female NPT x Female NPT	1 1/2	(38)	300	(2065)
SD-PRV205	Female NPT x Male NH Female NPT x Female NPT Rc x M78x2	2 1/2	(64)	175	(1205)
SD-PRV205	Female NPT x Male NH Female NPT x Female NPT Rc x M78x2	2 1/2	(64)	300	(2065)

## Details

Category	Hose Valves, Angle
Class of Work	1521 - Angle Hose Valves
Approval Standard	FM 1521, 1522 - Angle and Straightaway Hose Valves
Certification Type	FM Approved
Listing Country	United Kingdom

## Company

Shield Fire Safety and Security Ltd  
Unit 3 Endeavor Drive, Basildon, Essex, SS14  
3WF, United Kingdom  
<http://www.shieldglobal.com>

Additional Info

Hydrants & Hoses

Hose Valves

Hose valves of 1 ½ in. (38 mm) may be used on connections from sprinkler systems; 2 ½ in. (64 mm) valves are used on hose standpipes and fire pump headers. For pressures above 175 psi (1205 kPa), an appropriate pressure reducing device shall be used.

Hose Valves, Angle