

# Model SD-P1

## Product Description

*Air or Water Pressure Gauge - Model SD-P1, 3-1/2 in. (89 mm) size, Steel Case*

• 0 to 300 psi (0 to 2070 kPa)

This gauge has a 1/4 in. male BSPT or NPT bottom connection.

## Details

Category	Pressure Gauges
Class of Work	2311 - Air, Steam & Water Gauges
Approval Standard	FM 2311 - Vacuum and Pressure Gauges for Fire Protection Systems
Certification Type	FM Approved
Listing Country	United Kingdom

## Company

Shield Fire Safety and Security Ltd  
Unit 3 Endeavor Drive, Basildon, Essex, SS14  
3WF, United Kingdom  
<http://www.shieldglobal.com>

## Additional Info

### Automatic Sprinkler Systems

---

#### Pressure Gauges

Gauges for sprinkler systems and fire pumps are designed for use with air or water. These gauges are usually of the Bourdon tube type. The moving parts are fabricated of appropriate corrosion-resistant materials.

When installed on the air side of a dry pipe system, a retard type gauge may be used. This gauge is assembled with a tube appropriate to the unretarded pressure range of the gauge and is provided with a spring to resist the full scale load.

The two common sizes are 4 ½ and 3 ½ in. diameter. These gauges can be calibrated with a hydraulic testing unit by adjusting the dial pointer to read correctly at known pressures. Accuracy requirements are that the gauge be correct within 2% over the center third of its scale and within 3% over the remaining two-thirds. Dial marking subdivisions correspond to the maximum accuracy of the gauge.

For service on fire pumps where the suction may be taken under a lift, compound pressure vacuum gauges are available graduated in pressure units over both the pressure and vacuum scales, and are designed not to be injured by vacuum.

To minimize possible damage and provide maximum accuracy, gauges should be selected with scales of about twice the maximum system pressure.

---