

SIN SD2133

File Number: EX6699

COMPANY

SHIELD FIRE SAFETY & SECURITY LTD
Unit 3, Endeavour Dr
Basildon, SS14 3WF United Kingdom

SIN INFO

SD2133
Glass Bulb Type

ATTRIBUTES				
Response Type	Sprinkler Type	Nom K-Factor, gpm/vpsi (L/min/vbar)	System Working Pressure	Corrosion Resistant
SR	Standard Sidewall Spray Sprinklers	5.6 (80)	175 psig (1.2 Mpa)	Not Available

GENERAL	
Inlet Connection	
1/2 in. NPT	

STANDARD SIDEWALL SPRAY SPRINKLERS				
Type	Distance Below Ceiling, in. (cm)	Occupancy Hazard	Sprinkler Temp Rating, °F (°C)	Cover Temp Rating, °F (°C)
VSW	--	Light, Ordinary	155 (68), 175 (79), 200 (93)	Not Applicable



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."