







- **ROOF MONITOR**
 - Dual flow 5000/2500 LPM
 - Air Aspirated
- **BUMPER MONITOR**
 - · Adjustable flow up to 2650 LPM
 - · Air Aspirated

- **HOSE REEL**
 - 1.25 x 30m Water/Foam RHS
 - 1 x 30 DCP LHS
- WATER/FOAM TANK
 - GRP Construction
 - Water 10000L
 - Foam 1300L
- STORAGE LOCKER
 - Four(4) large capacity lockers, Two(2) on LH and RH sides
 - Dust and waterproof
 - Light alloy anodized roller shutter

- SIDE LINES
 - Four (4) nos. 2 on each side
 - · Restricted pressure with override.
- UNDERTRUCK **PROTECTION NOZZLE**
 - Seven Nozzle
 - Three Front/Two Middle/Two Rear
- **RESCUE AND FIREFIGHTING EQUIPMENTS**

Wide range of rescue and firefighting equipment/tools ICAO related standard tools can be provided.

- **REAR ACCESS LADDER**
 - Fixed ladder located the rear of the vehicle with non-slip threads.
- **ENGINE COMPARTMENT**
 - GRP Panel
 - Support minimum 100kg tools/equipment per compartment
 - · Corrosion resistant tubes
 - · Two upward lifting doors
- **TANK FILLING**

4 x 2.5", Two(2) on each side by hydrant



- **NAFFCO CREW CAB**
 - LH or RH steering position
 - Up to six(6) seating capacity
 - · Driver seat with air suspension
 - Crew seat with SCBA bracket
 - · Heavy duty gray dura coat vinyl material.



CAPACITY

10,000 Liters

DCP ///////// 250 Kg



CHASSIS

Torque





