

# DUAL SWITCH MONITOR MODULE



S-A5042



## TECHNICAL DATA

All data is supplied subject to change without notice. Specifications are typical at 24 V, 73°F and 50% RH unless otherwise stated.

### GENERAL

Product Operating Temperature	32°F to 120°F
Humidity	10% to 93% RH (no condensation or icing)
Standards and Approvals	UL
Dimensions	4.9"W x 4.9"H x 1.175" D
Materials	UL 94 V-0 polycarbonate
Wire Size	12-24 AWG

### LED STATUS

LED Color	Description
Green	Polling
Yellow (solid)	Isolation
Red	Alarm

### SIGNAL LINE CIRCUIT (SLC) - SUPERVISED POWER LIMITED

Supply Voltage	17 V to 28 V DC
Modulation Voltage	5 V - 9 V peak to peak
Supervisory Current	500 µA
Switch-on Surge Current	900 µA
Alarm/Operated Current, LED ON	1.6 mA per LED
Maximum Loop Current	1A

### INITIATING DEVICE CIRCUIT (IDC)

Wiring Styles	Supervised power limited Class A and Class B
Voltage	3.3 V DC (< 200 µA)
Line Impedance	100 Ω max
End-of-Line Resistors*	47k Ω

## PRODUCT OVERVIEW

Product	Dual Switch Monitor Module
Part No.	S-A5042

## PRODUCT INFORMATION

The Dual Input Monitor Module is a loop-powered device incorporating a dual monitored input circuit for connection to remote switches, for indoor use only.

- Built-in isolator.
- Visible LEDs.
- Loop Powered.
- Ground fault detection.
- Selectable priority to monitor equipment where a fast response is required.
- Interrupt facility.
- Improved design for ease of wiring.