

# NAC MODULE



**S-A5044**



## PRODUCT OVERVIEW

Product	NAC Module
Part No.	S-A5044

## PRODUCT INFORMATION

The NAC Module enables sounders to be operated continuously or be pulsed. Sounders may be operated individually or in groups and whichever address mode has been applied may be synchronized when in pulsed operation.

- Built-in isolator.
- Visible LEDs.
- Loop Powered.
- Can be used for public address speakers.
- Power supply health monitoring.
- Reverse polarity detection.
- Active short circuit detection (panel/power supply dependent).
- AC/DC monitoring (limited by wire length).
- Improved design for ease of wiring.

## TECHNICAL DATA

All data is supplied subject to change without notice. Specifications are typical at 24 V, 73°F and 50% RH unless otherwise stated.

### GENERAL

Product Operating Temperature	32°F to 120°F
Humidity	10% to 93% RH (no condensation or icing)
Standards and Approvals	UL
Dimensions	4.9"W x 4.9"H x 1.175" D
Materials	UL 94 V-0 polycarbonate
Wire Size	12-24 AWG

### LED STATUS

LED Color	Description
Green	Polling
Yellow (solid)	Isolation
Red	Alarm

### SINGLE LINE CIRCUIT (SLC) - SUPERVISED POWER LIMITED

Supply Voltage	17 V to 28 V DC
Modulation Voltage	5 V - 9 V peak to peak
Supervisory Current	500 µA
Switch-on Surge Current	900 µA
Alarm/Operated Current, LED ON	1.6 mA per LED
Maximum Loop Current	1A

### NOTIFICATION APPLIANCE CIRCUIT (NAC)

Wiring Styles	Supervised power limited Class A and Class B
End-of-Line Resistors*	47k Ω
Max (NAC)	Regulated 24 V DC, 2 A Use of regulated power limited DC supply that is listed for fire protection applications. The maximum number of connected devices must be within the output rating.
Max (Speakers)	70.7 V rms, 500 mA with wire supervision capability as per NFPA requirements. The speakers used must be listed for fire protection applications.